

Selection form of Rotary Table / Indexing Table

Machine Specification	Brand		Model	
	Controller	<input type="checkbox"/> Fanuc <input type="checkbox"/> Mitsubishi <input type="checkbox"/> Siemens <input type="checkbox"/> Heidenhain <input type="checkbox"/> Fagor <input type="checkbox"/> Other		
	Driver for 4 th Axis and cable	<input type="checkbox"/> No	<input type="checkbox"/> Driver + Cable (Electric cabinet to connector)	<input type="checkbox"/> Software and PLC for 4 th Axis
Dimension of working table	Dimension : T - slot : Width mm * Pitch mm * Number			
Rotary Table / Indexing Table	Model of Rotary Table : _____			
	Model of Indexing Table : _____		Minimum input increment : <input type="checkbox"/> 1° / <input type="checkbox"/> 5°	
Motor mounting position	<input type="checkbox"/> Right (R) <input type="checkbox"/> Left (L) <input type="checkbox"/> Back (RB)			
Position of cable connection	<input type="checkbox"/> Right	<input type="checkbox"/> Back	<input type="checkbox"/> Up	<input type="checkbox"/> Left
Model of Servomotor (Optional)	Fanuc	Mitsubishi	Siemens	Other_____
	<input type="checkbox"/> Straight Shaft <input type="checkbox"/> Taper Shaft	<input type="checkbox"/> Straight Shaft <input type="checkbox"/> Taper Shaft	<input type="checkbox"/> Straight Shaft <input type="checkbox"/> Taper Shaft	<input type="checkbox"/> Straight Shaft <input type="checkbox"/> Taper Shaft
Model of Driver (Optional)	Fanuc	Mitsubishi	Siemens	Other_____
Connector of Power and Signal Cable	<input type="checkbox"/> Standard Connector (Japanese Standard)	<input type="checkbox"/> Adherent connector (Euro Standard)	<input type="checkbox"/> Direct connect without connector	
Tailstock (Optional)	<input type="checkbox"/> Manual Tailstock MTS	<input type="checkbox"/> Hydraulic Auto Tailstock ATS	<input type="checkbox"/> Pneumatic Auto Tailstock ATS	
	<input type="checkbox"/> Support Tailstock with Hydraulic clamping BTS	<input type="checkbox"/> Support Tailstock with Pneumatic clamping BTS		
Power of PHC (Optional)	<input type="checkbox"/> AC220V	<input type="checkbox"/> AC110V	<input type="checkbox"/> DC24V	
Hydraulic Unit (Optional)	<input type="checkbox"/> 1HPx4P, 12L/min, 40L Single circuit solenoid valve for NCT only	<input type="checkbox"/> 2HPx4P, 30L/min, 70L Double circuit solenoid valve for HC only	<input type="checkbox"/> Other_____	
Other accessories (Optional)	<input type="checkbox"/> Chuck	<input type="checkbox"/> Pneumatic Chuck, Model: <input type="checkbox"/> Manual Chuck, Model: <input type="checkbox"/> Hydraulic Chuck, Model:		
	<input type="checkbox"/> Oil manifold	Specification: Input / Output		
	<input type="checkbox"/> DNS Controller Power 220V/3PH	Model:		
Language of operation manual	<input type="checkbox"/> Chinese	<input type="checkbox"/> English	<input type="checkbox"/> Other_____	